

UNCLASSIFIED

AD 408 449

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

CLASSIFIED BY DDC

AS AD NO. 408



408 449

TECHNICAL PAPER 63-9

AN OBJECTIVE AID FOR FORECASTING  
STRONG AND GUSTY SURFACE WINDS

at  
Paine AFB, Washington

Best Available Copy

AN OBJECTIVE AID FOR FORECASTING  
STRONG AND GUSTY SURFACE WINDS

at

Paine AFB, Washington

Revised June 1963

Prepared by:  
Thomas H. Simmonds  
Scientific Services Section  
Headquarters, 4th Weather Wing (MATS)  
Ent AFB, Colorado Springs, Colorado

## INTRODUCTION

Forecasting the occurrence of operationally critical values of strong surface winds with accompanying gusts presents a major problem at Paine AFB, Washington. This investigation was conducted to develop an objective aid for forecasting such critical values. (Revised June 1963)

## THE PROBLEM

The problem concerns the forecasting of strong southwesterly (see comments) surface winds with gusts greater than 25 knots during the months of December through March.

1. Observation times from which forecasts are made: 0000Z and 1200Z.
2. Valid period of forecast: 6 to 12 hours after each forecast is made.

## PERIOD OF DATA AND ANALYSIS CONDUCTED

The data sample used in this study included selected months December through March, 1956 through 1960. (See comments) The criteria to be met and the attached diagram are self-explanatory and their use is discussed under "Procedure."

## COMMENTS

1. Since a limited amount of data were used in the preparation of this technique, it may or may not prove to contain a representative sample. It rests with the user continually to add current data and refinements through experience to increase its accuracy and usability.
2. In order to prepare properly an objective method of this type, it is necessary to work with an exact statement of the problem. This must contain definitely established meteorological and time limits. However, the final product is not so sensitive that it will always cut on and off exactly within the limits specified. We observed on several occasions that the method gave "near misses" which were sufficiently close to be of value to the operational forecast. Information, other than that evidenced by a statistical verification, can be obtained through the forecaster's interpretation of the results of this type of study; i.e., it is recommended that the main role of this objective aid be that of a guide and that it be modified by the forecaster in those cases where he has information other than that used by the technique.
3. This technique is not reliable for forecasting winds with an easterly component.

## FORECAST CHECKLIST

Date \_\_\_\_\_

### Data Required

- |  |       |
|--|-------|
| (a) ZT (Port Hardy) sea-level pressure | _____ |
| (b) PDX (Portland) sea-level pressure  | _____ |
| (c) TCM (McChord) sea-level pressure   |       |
| (d) (PDX - TCM)pp                      | _____ |
| (e) TTI (Tatoosh) sea-level pressure   | _____ |
| (f) (TCM - TTI)pp                      | _____ |
| (g) PAE (Paine) sea-level pressure     | _____ |
| (h) (PAE - ZT)pp                       | _____ |
| (i) MSO (Missoula) sea-level pressure  | _____ |
| (j) (MSO - TTI)pp                      | _____ |

### Procedure

Steps in this procedure are sequential and must be followed in the order listed.

#### Step No

- |  |       |
|--|-------|
| 1. If $ZT_{pp} > 1022.8$ mbs, forecast "no" and stop   | _____ |
| 2. If $(PDX - TCM)_{pp} < +0.4$ mbs, forecast "no" and stop  | _____ |
| 3. If $(TCM - TTI)_{pp} > +6.0$ mbs, forecast "yes" and stop   | _____ |
| 4. If $(PAE - ZT)_{pp} < +2.8$ mbs, forecast "no" and stop   | _____ |
| 5. If $(MSO - TTI)_{pp} > +16.5$ mbs, forecast "yes" and stop  | _____ |
| 6. If $(MSO - TTI)_{pp} < +6.0$ mbs, forecast "no" and stop  | _____ |
| 7. If none of the above criteria are satisfied, use Diagram I. If case falls in Area "A," forecast "yes," and if in Area "B," forecast "no." |       |

